



North American EDM Supplies

4277 Hamann Parkway * Willoughby, Ohio 44094

Phone (440) 918-3770 * Toll Free (800) 270-2627 * Fax (440) 918-3838

Sales@edmsupplies.com



Pro900 Zinc Coated Wire

Benefits

- Precise Diameter (+0, -0.002mm)
- This wire has a special coating to enhance cutting speeds and surface quality.
- Stable coating state
- This wire is designed to operate at higher speeds than traditional wire.
- The surface quality will be much higher than traditional hard brass wire.
- This wire burns extremely clean and has a very smooth wire surface.

PRO900 – Wire Specifications								
Type	Item #	Dimensions		Tensile Strength		Elongation	Conductivity (IACS)	Color
Hard Brass Wire	PRO-20H	0.008"	0.20mm	±900N/mm ²	130K PSI	3%	21%	SILVER
	PRO-25H	0.010"	0.25mm					
	PRO-30H	0.012"	0.30mm					
Soft Brass Wire	PRO-20S	0.008"	0.20mm	±490N/mm ²	64-78K PSI	15%		
	PRO-25S	0.010"	0.25mm					
	PRO-30S	0.012"	0.30mm					

PRO900 – Spool Size Chart				
Machine Type	Spool Type	0.20mm	0.25mm	0.30mm
Japanese Machines	P-3	*	*	*
	P-5	*	*	*
	P-10	*	*	*
	P-20	*	*	*
European Machines	D-125	*	*	*
	D-160	*	*	*
	D-200	*	*	*